

Safety Data Sheet Screw Cleaning Spray

baederlacke.eu



Safety Data Sheet

according to UK REACH Regulation

Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Bäder - Screw Cleaning Spray 400 ml

```
UFI:
```

3F89-Q878-N005-SRKU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Maintainer, irritant, containing solvents with skin absorptive substances

1.3. Details of the supplier of the safety data sheet

Company name:	Lackfabrik Bäder GmbH & Co KG	
Street:	Dieselstraße 34	
Place:	D-73734 Esslingen	
Telephone:	+49 711 381607	Telefax: +49 711 383092
E-mail:	info@lackfabrik-baeder.de	
Contact person:	Moritz Storch	
E-mail:	info@lackfabrik-baeder.de	
Internet:	www.baederlacke.eu	
1.4. Emergency telephone	Call NHS 111 or a doctor	

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

Danger

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane

Signal word: Pictograms:

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Precautionary	/ statements

ecautionary statement	is
P102	Keep out of reach of children.
P210	Keep away from heat. No Smoking.
P211	Do not spray on an open flame or other ignition source.
P211	Do not spray on an open flame or other ignition sour



Safety Data Sheet

according to UK REACH Regulation

	: 27.02.2024	Product code: 92895	Page 2 of 1
DOGA			
P251 P410-	-D/12	Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F	=
Special la	belling of certa	Restricted to professional users.	
l abelling	of packages w	vhere the contents do not exceed 125 ml	
Signal wo		Danger	
Pictogran	ns:		
Hazard st			
	H229-H336		
	nary statemen		
		51-P410+P412	
2.3. Other ha			
	urised containe	er: May burst if heated.	
Press		•	
Press	Compositio	n/information on ingredients	
Press	Compositio	•	
Press SECTION 3 3.2. Mixtures Chemical	Composition	n/information on ingredients	
Press SECTION 3 3.2. Mixtures Chemical	Composition	n/information on ingredients	
Press SECTION 3 3.2. Mixtures Chemical	Composition	n/information on ingredients	
Press SECTION 3 3.2. Mixtures Chemical Stripp	Composition	n/information on ingredients	Quantity
Press SECTION 3 3.2. Mixtures Chemical Stripp Hazardous o	characterization characterization er, irritant, contactoritation	n/information on ingredients	Quantity
Press SECTION 3 3.2. Mixtures Chemical Stripp Hazardous o	characterization characterization er, irritant, conta components Chemical nam EC No	n/information on ingredients on taining solvents with skin absorptive substances	Quantity
Press SECTION 3 3.2. Mixtures Chemical Stripp Hazardous o CAS No	Characterization characterization er, irritant, conta components Chemical nam EC No Classification	n/information on ingredients ion taining solvents with skin absorptive substances ne Index No REACH No	Quantity 50 - 100 %
Press SECTION 3 3.2. Mixtures Chemical Stripp Hazardous o	Characterization characterization er, irritant, conta components Chemical nam EC No Classification	n/information on ingredients on taining solvents with skin absorptive substances ne Index No REACH No (GB CLP Regulation)	

	H411				
109-87-5	Dimethoxymethane				
	203-714-2				
	Flam. Liq. 2; H225	-			
124-38-9	carbon dioxide				
	204-696-9				
	Compressed gas; H280	-			

Full text of H and EUH statements: see section 16.

Specific Con	c. Limits, M-fa	ctors and ATE					
CAS No	EC No	Chemical name	Quantity				
	Specific Conc. Limits, M-factors and ATE						
64742-49-0	921-024-6	921-024-6 Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane					
	inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg						
109-87-5	203-714-2	Dimethoxymethane	10 - 20 %				
	dermal: LD50	= > 5000 mg/kg; oral: LD50 = 6423 mg/kg					

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

SECTION 4: First aid measures



Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 3 of 11

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of water. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation. Causes eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.



Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 4 of 11

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. After work, wash hands and face. When using do not eat or drink.

Further information on handling

When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

7.3. Specific end use(s)

Stripper, irritant, containing solvents with skin absorptive substances

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
109-87-5	Dimethoxymethane	1000	3160		TWA (8 h)	WEL
		1250	3950		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL



Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 5 of 11

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
64742-49-0	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane						
Worker DNEL, long-terminhalationsystemic2035 mg/m³							
Worker DNEL,	long-term	dermal	systemic	773 mg/kg bw/day			
64-17-5	ethanol						
Worker DNEL,	long-term	inhalation	systemic	950 mg/m³			
Worker DNEL,	long-term	dermal	systemic	343 mg/kg bw/day			
Consumer DN	EL, long-term	inhalation	systemic	114 mg/m³			
Consumer DN	EL, long-term	dermal	systemic	206 mg/kg bw/day			
Consumer DN	EL, long-term	oral	systemic	87 mg/kg bw/day			
109-87-5	Dimethoxymethane						
Worker DNEL,	long-term	inhalation	systemic	126,6 mg/m ³			
Worker DNEL,	long-term	dermal	systemic	17,9 mg/kg bw/day			
Consumer DN	EL, long-term	inhalation	systemic	31,5 mg/m ³			
Consumer DNEL, long-term		dermal	systemic	18,1 mg/kg bw/day			
Consumer DN	EL, long-term	oral	systemic	18,1 mg/kg bw/day			

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater	(intermittent releases)	2,75 mg/l
Marine wate	r	0,79 mg/l
Freshwater	sediment	3,6 mg/kg
Marine sedi	ment	2,9 mg/kg
Secondary	poisoning	380 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	580 mg/l
Soil		0,63 mg/kg
109-87-5	Dimethoxymethane	
Freshwater		14,577 mg/l
Marine wate	r	1,477 mg/l
Freshwater	13,135 mg/kg	
Micro-organ	isms in sewage treatment plants (STP)	10000 mg/l
Soil		4,654 mg/kg

8.2. Exposure controls





Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 6 of 11

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles EN 166

Hand protection

Tested protective gloves must be worn.

Suitable material: NBR (Nitrile rubber).

Thickness of the glove material > 0,4mm

penetration time (maximum wearing period): > 480 min. EN ISO 374

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. Filtering device with filter or ventilator filtering device of type: A (EN 14387)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	colourless	
Odour:	characteristic	
Melting point/freezing point:		not applicable
Boiling point or initial boiling point and		41 °C
boiling range:		
Lower explosion limits:		0,8 vol. %
Upper explosion limits:		17,6 vol. %
Flash point:		-18 °C
Auto-ignition temperature:		200 °C
pH-Value:		not applicable
Vapour pressure:		426 hPa
(at 20 °C)		
Density:		0,75 g/cm³
9.2. Other information		

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

SECTION 10: Stability and reactivity

10.1. Reactivity

Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent, strong



Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 7 of 11

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

The product is chemically stable under recommended conditions of storage, use and temperature.

10.5. Incompatible materials

Reacts with : Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon dioxide (CO2), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64742-49-0	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane							
	oral	LD50 mg/kg	>5000	Rat		OECD 401		
	dermal	LD50 mg/kg	>2000	Rat		OECD 402		
	inhalation (4 h) vapour	LC50	>20 mg/l	Rat		OECD 403		
109-87-5	Dimethoxymethane							
	oral	LD50 mg/kg	6423	Rat	Study report (1982)	OECD Guideline 423		
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1989)	OECD Guideline 402		

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available



Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 8 of 11

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

SECTION 12: Ecological information

12.1. Toxicity

Do not allow to enter into surface water or drains.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method			
109-87-5	Dimethoxymethane	Dimethoxymethane								
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Danio rerio	Study report (1991)	OECD Guideline 203			
	Acute algae toxicity	ErC50 mg/l	9120	72 h	Pseudokirchneriella subcapitata	Study report (2015)	other: REACH guidance on QSAR R6, May 20			
	Acute crustacea toxicity	EC50 mg/l	> 1200	48 h	Daphnia magna	Study report (1991)	OECD Guideline 202			
	Fish toxicity	NOEC mg/l	450,281	30 c	not relevant	Study report (2012)	other: REACH guidance on QSAR R6, May 20			
	Algae toxicity	NOEC mg/l	145,77	30 c	lalgae	Study report (2012)	other: REACH guidance on QSAR R6, May 20			
	Crustacea toxicity	NOEC mg/l	150,5	30 c	Daphnia magna	Study report (2012)	other: REACH guidance on QSAR R6, May 20			

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name					
109-87-5	Dimethoxymethane	Dimethoxymethane				
BCF						
CAS No	Chemical name	BCF	Species	Source	Source	
109-87-5	Dimethoxymethane	0,6		REACh Reg	REACh Registration D	

12.4. Mobility in soil

Product is easily volatile.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 9 of 11

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F



Revision date: 27.02.2024	Bäder - Screw Cleaning Spray 400 ml Product code: 92895	Page 10 of 11
Special Provisions:	190 327 344 625	
Limited quantity:	1 L	
Excepted quantity:	E0	
Marine transport (IMDG)		
<u>14.1. UN number or ID number:</u>	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Special Provisions:	63, 190, 277, 327, 344, 959	
Limited quantity:	1000 mL	
Excepted quantity:	E0	
EmS:	F-D, S-U	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 1950	
14.2. UN proper shipping name:	AEROSOLS	
<u>14.3. Transport hazard class(es):</u>	2.1	
14.4. Packing group:	-	
Hazard label:	2.1	
Special Provisions:	A145 A167 A802	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:	203	
IATA-max. quantity - Passenger:	75 kg	
IATA-packing instructions - Cargo:	203	
IATA-max. quantity - Cargo:	150 kg	
SECTION 15: Regulatory information		

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information				
Restrictions on use (REACH, annex XVII):				
Entry 3, Entry 29, Entry 40				
2010/75/EU (VOC):	94,8 % (711 g/l)			
National regulatory information				
Water hazard class (D):	2 - obviously hazardous to water			
15.2. Chemical safety assessment				
Chemical safety assessments for substances in this mixture were not carried out.				

SECTION 16: Other information



Bäder - Screw Cleaning Spray 400 ml

Revision date: 27.02.2024

Product code: 92895

Page 11 of 11

Abbreviations and acronyms

Aerosol: Aerosols Compressed gas: Compressed gas Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation STOT SE: Specific target organ toxicity - single exposure Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Washing and cleaning products	IS, PW, C	-	35	7, 11, 19, 28	4, 8d	-	105	
LCS: Life cycle stages SU: Sectors of use									
PC: Product categories				F	PROC: Process categories				
ERC: Environmental release categories				A	AC: Article categories				
TF: Technical functions									

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)