



Safety data sheet

Fast Dry Range

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: SSL FastDry
Print date: 13.08.2024
Version: 3

Schraubensicherungslack
Revision date: 13.08.2024
Issue date: 13.08.2024

EN
Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): SSL FastDry
Trade name/designation: Schraubensicherungslack
Fast Dry
UFI: P600-604V-S000-53DR

Schraubensicherungslack Fast Dry (fast drying tamper proof sealant):

Basic: White 11000f; Yellow 12000f; Orange 12200f; Red 13000f; Pink 13200f; Blue 14000f; Green 15000f; Grey 17000f; Black 18000f

Secure: White 11002f; Yellow 12002f; Orange 12202f; Red 13002f; Pink 13202f

Topsecure: White 11001f; Yellow 12001f; Orange 12201f; Red 13001f; Pink 13201f; Blue 14001f; Green 15001f

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

SCHRAUBEN-SICHERUNGSLACK Tamper proof varnish/sealant. Not to be used as glue/adhesive!

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Lackfabrik Bäder GmbH & Co. KG.

Dieselstraße 34

D-73734 Esslingen/Neckar

Telephone: +49 (0) 711/381607

Telefax: +49 (0) 711/383092

Department responsible for information:

Department responsible for information: info@lackfabrik-baeder.de

1.4. Emergency telephone number

Emergency telephone number +49 (0) 711/381607

Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

STOT SE 3 / H336

STOT-single exposure

May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P261 Avoid breathing vapours.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves and eye protection/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: SSL FastDry
Print date: 13.08.2024
Version: 3

Schraubensicherungslack
Revision date: 13.08.2024
Issue date: 13.08.2024

EN
Page 2 / 9

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Keep locked up.

Hazard components for labelling
n-butyl acetate

Supplemental hazard information
EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. **Other hazards**

No information available.

SECTION 3: Composition/information on ingredients

3.2. **Mixtures**

*

Description

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

| EC No. CAS No. Index No. | REACH No. Designation classification: // Remark | weight-% |
|--|---|----------|
| 204-658-1 123-86-4 607-025-00-1 | 01-2119485493-29 n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336 / EUH066 | 20 - 25 |
| 205-500-4 141-78-6 607-022-00-5 | Ethyl acetate Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066 | 20 - 25 |
| 215-535-7 1330-20-7 601-022-00-9 | 01-2119488216-32 Xylene Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226 Acute toxicity estimate (ATE): ATE (dermal): 2000 mg/kg bw | 5 - 10 |
| 200-661-7 67-63-0 603-117-00-0 | 01-2119457558-25 propan-2-ol Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 | 2,5 - 5 |

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm.

Article No.: SSL FastDry
Print date: 13.08.2024
Version: 3

Schraubensicherungslack
Revision date: 13.08.2024
Issue date: 13.08.2024

EN
Page 3 / 9

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: SSL FastDry Schraubensicherungslack
Print date: 13.08.2024 Revision date: 13.08.2024
Version: 3 Issue date: 13.08.2024

EN
Page 4 / 9

from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

MEL/OES, TWA: 724 mg/m³; 150 ppm

MEL/OES, STEL: 966 mg/m³; 200 ppm

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

WEL, TWA: 734 mg/m³; 200 ppm

WEL, STEL: 1468 mg/m³; 400 ppm

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

propan-2-ol

Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

TWA: 999 mg/m³; 400 ppm

STEL: 1250 mg/m³; 500 ppm

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

propan-2-ol

Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

DNEL long-term dermal (systemic), Workers: 888 mg/kg

DNEL long-term inhalative (systemic), Workers: 500 mg/m³

PNEC:

propan-2-ol

Index No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

PNEC aquatic, freshwater: 140,9 mg/L

PNEC aquatic, marine water: 140,9 mg/L

PNEC aquatic, intermittent release: 140,9 mg/L

PNEC sediment, marine water: 552 mg/kg

PNEC, soil: 28 mg/kg

PNEC sewage treatment plant (STP): 2251 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Unsuitable material: NR (natural rubber, Natural latex)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: SSL FastDry
Print date: 13.08.2024
Version: 3

Schraubensicherungslack
Revision date: 13.08.2024
Issue date: 13.08.2024

EN
Page 5 / 9

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties *

| | |
|---|--|
| Physical state: | Liquid |
| Colour: | refer to label |
| Odour: | characteristic |
| Odour threshold: | not determined |
| Melting point/freezing point: | not determined |
| Initial boiling point and boiling range: | 76 °C Source: Ethyl acetate |
| Flammability: | Highly flammable liquid and vapour. |
| Lower and upper explosion limit: | |
| Lower explosion limit: | 1,1 Vol-% Source: Xylene |
| Upper explosion limit: | 12 Vol-% Source: propan-2-ol |
| Flash point: | -4 °C |
| Auto-ignition temperature: | 370 °C Source: n-butyl acetate |
| Decomposition temperature: | not determined |
| pH at 20 °C: | not applicable |
| Kinematic viscosity (40°C): | 28190,19 mm²/s |
| Viscosity at 20 °C: | 30000 mPa* s |
| Solubility(ies): | |
| Water solubility at 20 °C: | insoluble |
| Partition coefficient: n-octanol/water: | see section 12 |
| Vapour pressure at 20 °C: | 27,4 mbar |
| Density and/or relative density: | |
| Density at 20 °C: | 1,06 g/cm³ |
| Relative vapour density: | not determined |
| particle characteristics: | not applicable |

9.2. Other information *

| | |
|--------------------------|--------------------|
| Solid content: | 44 weight-% |
| solvent content: | |
| Organic solvents: | 56 weight-% |
| Water: | 0 weight-% |

SECTION 10: Stability and reactivity

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: SSL FastDry
Print date: 13.08.2024
Version: 3

Schraubensicherungslack
Revision date: 13.08.2024
Issue date: 13.08.2024

EN
Page 6 / 9

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 *

Acute toxicity

Xylene

oral, LD50, Rat: 8700 mg/kg

dermal, LD50, Rabbit: 2000 mg/kg

inhalative (Gases), LC50, Rat: 6350 ppmV (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: SSL FastDry Schraubensicherungslack
Print date: 13.08.2024 Revision date: 13.08.2024
Version: 3 Issue date: 13.08.2024

EN
Page 7 / 9

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID):

FARBZUBEHÖRSTOFFE

Sea transport (IMDG):

PAINT RELATED MATERIAL

Air transport (ICAO-TI / IATA-DGR):

Paint related material

14.3. Transport hazard class(es)

3

14.4. Packing group

Land transport (ADR/RID):

III

for packages > 450 litres:

II

Sea transport (IMDG):

III

for packages > 450 litres

II

Air transport (ICAO-TI / IATA-DGR):

III

for packages > 30 litres:

II

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

E

for packages > 450 litres:

D/E

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: SSL FastDry
 Print date: 13.08.2024
 Version: 3

Schraubensicherungslack
 Revision date: 13.08.2024
 Issue date: 13.08.2024

EN
 Page 8 / 9

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture *

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 596

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
 Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

Not listed in TOXIC SUBSTANCES CONTROL ACT (TSCA)

15.2. Chemical Safety Assessment *

For the following substances of this mixture a chemical safety assessment has been carried out:

| EC No. CAS No. | Designation | REACH No. |
|------------------------|-----------------|------------------|
| 204-658-1 123-86-4 | n-butyl acetate | 01-2119485493-29 |
| 215-535-7 1330-20-7 | Xylene | 01-2119488216-32 |
| 200-661-7 67-63-0 | propan-2-ol | 01-2119457558-25 |

SECTION 16: Other information *

Full text of classification in section 3:

| | | |
|----------------------|-----------------------------------|---|
| Flam. Liq. 3 / H226 | Flammable liquids | Flammable liquid and vapour. |
| STOT SE 3 / H336 | STOT-single exposure | May cause drowsiness or dizziness. |
| Flam. Liq. 2 / H225 | Flammable liquids | Highly flammable liquid and vapour. |
| Eye Irrit. 2 / H319 | Serious eye damage/eye irritation | Causes serious eye irritation. |
| Acute Tox. 4 / H312 | Acute toxicity (dermal) | Harmful in contact with skin. |
| Acute Tox. 4 / H332 | Acute toxicity (inhalative) | Harmful if inhaled. |
| Skin Irrit. 2 / H315 | Skin corrosion/irritation | Causes skin irritation. |
| Asp. Tox. 1 / H304 | Aspiration hazard | May be fatal if swallowed and enters airways. |

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

| | | |
|--------------|-----------------------------------|------------------------|
| Flam. Liq. 2 | Flammable liquids | On basis of test data. |
| Eye Irrit. 2 | Serious eye damage/eye irritation | Calculation method. |
| STOT SE 3 | STOT-single exposure | Calculation method. |

Abbreviations and acronyms

| | |
|----------|--|
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| OEL | Occupational Exposure Limit Value |
| BLV | Biological Limit Value |
| CAS | Chemical Abstracts Service |
| CLP | Classification, Labelling and Packaging |
| CMR | Carcinogenic, Mutagenic and Reprotoxic |
| DIN | German Institute for Standardization / German industrial standard |
| DNEL | Derived No-Effect Level |
| EAKV | European Waste Catalogue Directive |
| EC | Effective Concentration |
| EC | European Community |
| EN | European Standard |
| IATA-DGR | International Air Transport Association – Dangerous Goods Regulations |
| IBC Code | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in |

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: SSL FastDry
Print date: 13.08.2024
Version: 3

Schraubensicherungslack
Revision date: 13.08.2024
Issue date: 13.08.2024

EN
Page 9 / 9

| | |
|-----------|---|
| ICAO-TI | Bulk International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air |
| IMDG Code | International Maritime Code for Dangerous Goods |
| ISO | International Organization for Standardization |
| LC | Lethal Concentration |
| LD | Lethal Dose |
| MARPOL | Maritime Pollution: The International Convention for the Prevention of Pollution from Ships |
| OECD | Organisation for Economic Cooperation and Development |
| PBT | persistent, bioaccumulative, toxic |
| PNEC | Predicted No Effect Concentration |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| UN | United Nations |
| VOC | Volatile Organic Compounds |
| vPvB | very persistent and very bioaccumulative |

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version